



Opto Devices

LED Displays

CONTENTS

■ High Brightness LED Numeric Displays	P. E18
■ LED Numeric Displays	P. E18
Single Digit LED Numeric Displays (Surface Mount type)	P. E18
Single Digit LED Numeric Displays	P. E19
Two Digit LED Numeric Displays	P. E19
Three Digit LED Numeric Displays	P. E19

High Brightness LED Numeric Displays

High brightness, low power consumption, and high reliability.

High Brightness LED Numeric Displays																		
Shape	Part No.	Emitting Color	Absolute Maximum Ratings(Ta=25°C)				Absolute Maximum Ratings		Electrical and Optical Characteristics(Ta=25°C)									
			Power Dissipation P _o (mW)	Forward Current I _F (mA)	Peak Forward Current I _{FP} * (mA)	Reverse Voltage V _R (V)	Operating Temperature Topr (°C)	Storage Temperature Tstg (°C)	Forward Voltage V _F		Reverse Current I _R		Light Wavelength Peak Half-wave		Brightness/Digit I _v			
									Typ. (V)	I _F (mA)	Max. (μA)	V _R (V)	λ _p Typ. (nm)	Δλ Typ. (nm)	I _F (mA)	Min. (mcd)	Typ. (mcd)	I _F (mA)
Character Height:8mm External Dimensions:(7×11)	LAP-301VB/VL	Red													14	36		
	LAP-301MB/ML	Green	448	20	60	5	-25 to +75	-30 to +85	1.9	10	100	3	572	20	10	36	100	10
	LAP-301DB/DL	Orange											605			56	250	
Character Height:10.16mm External Dimensions:(9.6×13)	LAP-401VD/VN	Red													14	36		
	LAP-401MD/MN	Green	448	20	60	5	-25 to +75	-30 to +85	1.9	10	100	3	572	20	10	36	100	10
	LAP-401DD/DN	Orange											605			56	250	
Character Height:14.6mm External Dimensions:(12.5×19)	LAP-601VB/VL	Red													14	36		
	LAP-601MB/ML	Green	448	20	60	5	-25 to +75	-30 to +85	1.9	10	100	3	572	20	10	36	100	10
	LAP-601DB/DL	Orange											605			56	250	
Character Height:14.3mm External Dimensions:(25×19)	LBP-602VA2/VK2	Red													14	36		
	LBP-602MA2/MK2	Green	896	20	60	5	-25 to +75	-30 to +85	1.9	10	100	3	572	20	10	36	100	10
	LBP-602DA2/DK2	Orange											605			56	250	

Notes:*I_{FP} measured under duty ≤ 1/5, Pulse width ≤ 1ms

LED Numeric Displays

ROHM's LED numeric displays are compatible with automatic reflow processes.

Single Digit LED Numeric Displays(Surface Mount type)																		
Shape	Part No.	Emitting Color	Absolute Maximum Ratings(Ta=25°C)				Absolute Maximum Ratings		Electrical and Optical Characteristics(Ta=25°C)									
			Power Dissipation P _o (mW)	Forward Current I _F (mA)	Peak Forward Current I _{FP} * (mA)	Reverse Voltage V _R (V)	Operating Temperature Topr (°C)	Storage Temperature Tstg (°C)	Forward Voltage V _F		Reverse Current I _R		Light Wavelength Peak Half-wave		Brightness/Digit I _v			
									Typ. (V)	I _F (mA)	Max. (μA)	V _R (V)	λ _p Typ. (nm)	Δλ Typ. (nm)	I _F (mA)	Min. (mcd)	Typ. (mcd)	I _F (mA)
Character Height:8mm External Dimensions:(6.8×11)	LF-3011VA/VK	Red	320	15	60	5	-25 to +75	-30 to +85	2.0	10	100	3	650	40	10	3.6	10	10
	LF-3011MA/MK	Green	480	20					2.1				563					

Notes:*I_{FP} measured under duty ≤ 1/5, Pulse width ≤ 1ms

These single digit numeric displays are 8 to 25.4mm in height and available in a range of colors.

Single Digit LED Numeric Displays																		
Shape	Part No.	Emitting Color	Absolute Maximum Ratings(Ta=25°C)				Absolute Maximum Ratings		Electrical and Optical Characteristics(Ta=25°C)									
			Power Dissipation P _o (mW)	Forward Current I _F (mA)	Peak Forward Current I _{Fp} * (mA)	Reverse Voltage V _R (V)	Operating Temperature Topr (°C)	Storage Temperature Tstg (°C)	Forward Voltage V _F		Reverse Current I _R		Light Wavelength Peak Half-wave			Brightness/Digit I _v		
								Typ. (V)	I _F (mA)	Max. (μA)	V _R (V)	λ _p Typ. (nm)	λ _c Typ. (nm)	I _F (mA)	Min. (mcd)	Typ. (mcd)	I _F (mA)	
	LA-301VB/VL	Red	320	15	60			2.0	10			650	40	10	3.6	10		
	LA-301MB/ML	Green	480	20	60			2.1	10			563	40	10	5.6	16		
	LA-301AB/AL	High Brightness Red	520	25	50			2.05	20			626	18	20	36	90		
	LA-301EB/EL	High Brightness Orange	520	25	50			2.05	20			610	17	20	36	90		
	LA-401VD/VN	Red	320	15	60			2.0	10			650	40	10	5.6	16		
	LA-401MD/MN	Green	480	20	60			2.1	10			563	40	10	5.6	16		
	LA-401AD/AN	High Brightness Red	520	25	50			2.05	20			626	18	20	36	90		
	LA-401ED/EN	High Brightness Orange	520	25	50			2.05	20			610	17	20	36	90		
	LA-501VD/VN	Red				5	-25 to +75	-30 to +85	2.0		100	3	650					10
	LA-501MD/MN	Green							2.1				563					16
	LA-601VB/VL	Red	480	20	60				2.0	10			650	40	10			14
	LA-601MB/ML	Green							2.1				563					22
	LA-601AB/AL	High Brightness Red	520	25	50				2.05	20			626	18	20	36	90	
	LA-601EB/EL	High Brightness Orange	520	25	50				2.05	20			610	17	20	36	90	
	LA-101VA/VK	Red		15	60				4.0				650					3.6
	LA-101MA/MK	Green	640	20	60				4.2	10			563	40	10			5.6

Notes: *I_{Fp} measured under duty ≤ 1/5, Pulse width ≤ 1ms, High Brightness and Blue I_F measured under duty ≤ 1/10, Pulse width ≤ 0.1 ms 2) LA-101 series : order-based production

These two digit numeric displays are 10.16 to 14.3mm in height and available in a range of colors.

Two Digit LED Numeric Displays																		
Shape	Part No.	Emitting Color	Absolute Maximum Ratings(Ta=25°C)				Absolute Maximum Ratings		Electrical and Optical Characteristics(Ta=25°C)									
			Power Dissipation P _o (mW)	Forward Current I _F (mA)	Peak Forward Current I _{Fp} * (mA)	Reverse Voltage V _R (V)	Operating Temperature Topr (°C)	Storage Temperature Tstg (°C)	Forward Voltage V _F		Reverse Current I _R		Light Wavelength Peak Half-wave			Brightness/Digit I _v		
								Typ. (V)	I _F (mA)	Max. (μA)	V _R (V)	λ _p Typ. (nm)	λ _c Typ. (nm)	I _F (mA)	Min. (mcd)	Typ. (mcd)	I _F (mA)	
	LB-402VD/VN	Red	640	15				2.0				650			5.6	16		
	LB-402MD/MN	Green			60	5	-25 to +75	-30 to +85	2.1	10			563	40	10	9.0	25	
	LB-502VD/VN	Red	960	20				2.0				650			5.6	16		
	LB-502MD/MN	Green						2.1		100	3	563			9.0	25		10
	LB-602VA2/VK2	Red						2.0				650			5.6	16		
	LB-602MA2/MK2	Green						2.1	10			563	40	10	9.0	25		
	LB-602AA2/AK2	High Brightness Red				5	-25 to +75	-30 to +85					626	18				
	LB-602EA2/EK2	High Brightness Orange	1,040	25	50				2.05	20			610	17	20	36	90	

Notes: *I_{Fp} measured under duty ≤ 1/5, Pulse width ≤ 1ms, High Brightness and Blue I_F measured under duty ≤ 1/10, Pulse width ≤ 0.1 ms

Three Digit LED Numeric Displays																		
Shape	Part No.	Emitting Color	Absolute Maximum Ratings(Ta=25°C)				Absolute Maximum Ratings		Electrical and Optical Characteristics(Ta=25°C)									
			Power Dissipation P _o (mW)	Forward Current I _F (mA)	Peak Forward Current I _{Fp} * (mA)	Reverse Voltage V _R (V)	Operating Temperature Topr (°C)	Storage Temperature Tstg (°C)	Forward Voltage V _F		Reverse Current I _R		Light Wavelength Peak Half-wave			Brightness/Digit I _v		
								Typ. (V)	I _F (mA)	Max. (μA)	V _R (V)	λ _p Typ. (nm)	λ _c Typ. (nm)	I _F (mA)	Min. (mcd)	Typ. (mcd)	I _F (mA)	
	LB-603VF/VP	Red	960	15	60	5	-25 to +75	-30 to +85	2.0	10	100	3	650	40	10	5.6	16	10

Notes: *I_{Fp} measured under duty ≤ 1/5, Pulse width ≤ 1ms

